

Graffiti Removal Chart

SURFACE	REMOVAL PRODUCT	DIRECTIONS	OTHER
Brick, cement or concrete	Extra strength paint remover	Apply with wire brush. Let soak. Rinse with pressure hose.	Grit sandpaper can be used on flat surfaces (will scratch). Use sealer after removal.
Stucco	Paint remover	Use cloth or rag and rinse with pressure hose. Use stucco paint and go over graffiti carefully.	Consider sealer as a finishing coat.
Aluminim/vinyl siding	Experiment with paint remover (sparingly)	Constantly use a clean rag.	Will probably have to repaint.
Wood	Paint thinner, acetone, primer, paint	First try thinner or acetone. On latex or oil-based paint, use a stain -blocking primer. Repaint	Consider a sealer coat.
Fiberglass	Paint thinner	Work your way up the thinner list. Use full-strength and rinse carefully.	
Glass or plexi-glass	Razor blade, paint thinners	Scrape paint off carefully. If using solvents on plexi be careful to read the label to see if it is compatible with that surface as some will fog or mar plexi.	Rinse thoroughly with water.
Metal	Solvent, paint remover.	Constantly use a clean rag. If unsuccessful try paint remover.	
Etching	Fillers, Replace	Gouges in surfaces must be filled or replaced.	